## NSN 4720-01-492-5697

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-492-5697
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-50.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response
Outside Diameter:
Between 1.219 inches and 1.281 inches
Minimum Inside Bending Radius:
9.500 inches
End Application:
MEDI-UM-TAC-TICA
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
12400.0 pounds per square inch
Maximum Operating Pressure:
3100.0 pounds per square inch
Thread Size:
1.0625 inches 1st end
Seat Angle:
37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

6200.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Oil resistant and weatherproof

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

1450.0 millimeters

**Product Name:** 

Hose, hydraulic, high pressure

## NSN 4720-01-492-5697

No Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Material is carbon steel
Media For Which Designed:
$\label{thm:local_equation} \mbox{Hydraulic fluid, water base single response and hydraulic fluid single response}$
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: