

View Online at <https://aerobasegroup.com/nsn/4720-01-492-5697>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-50.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response

**Outside Diameter:**

Between 1.219 inches and 1.281 inches

**Minimum Inside Bending Radius:**

9.500 inches

**End Application:**

MEDI-UM-TAC-TICA

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

12400.0 pounds per square inch

**Maximum Operating Pressure:**

3100.0 pounds per square inch

**Thread Size:**

1.0625 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

6200.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

1450.0 millimeters

**Product Name:**

Hose, hydraulic, high pressure

**Special Features:**

Material is carbon steel

**Media For Which Designed:**

Hydraulic fluid, water base single response and hydraulic fluid single response

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0