Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-492-9131

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
2.500 inches
End Application:
Cons ground support equipment
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
1400.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer braided textile yarn
Maximum Operating Pressure:
350.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.000 inches
Special Features:
Using parker fitting p/n 31382-2-4
Media For Which Designed:
Fuel/oil, hydrocarbon and water single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

