

View Online at <https://aerobasegroup.com/nsn/4720-01-493-6461>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response

Outside Diameter:

0.469 inches

Minimum Inside Bending Radius:

4.000 inches

End Application:

Mk105 mod 4, helicopter installation

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Unthreaded external hose 2nd end

Thready Qty Per Inch (tpi):

28 1st end

Burst Test Pressure:

1250.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 1st layer molded rubber

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and hydraulic solution resistant and oil resistant and alcohol resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

114.000 inches and 126.000 inches

Seat Radius:

0.295 inches 1st end

Product Name:

Hose assembly, vent

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Special Test Features:

Low temps and low pressure

Thread Series Designator:

Unf 1st end

Specification Data:

53722-mil-a-38726 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0