NSN 4720-01-493-7705

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-493-7705

Round			
Thread Class:			
2a 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.250 inches			
Tempurature Rating:			
-25.0 degrees fahrenheit and 300.0 degrees fahrenheit single response			
Outside Diameter:			
0.600 inches			
Minimum Inside Bending Radius:			
4.000 inches			
Connection Style:			
Swivel, external seat for gasket seal 2nd end			
End Connection Design:			
Straight 2nd end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
20000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided wire and 2nd layer braided wire and outer layer wrapped rubber, synthetic			
Maximum Operating Pressure:			
5000.0 pounds per square inch			
Thread Size:			
0.438 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Outer Covering Environmental Protection:			
Waterproof and oil resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
5.000 inches			
Product Name:			
Hose assembly			
Special Features:			
Consists of hose (gh793-4 or 381-4) and fittings 1aa4fj4 or 10643-4-4 and 1aa4mb4 or 10543-4-4			
Media For Which Designed:			
Hydraulic fluid and hydraulic fluid, water base single response			

NSN 4720-01-493-7705

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Carias	Decimates
illieau	oenes	Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0