Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-494-0128

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
9.5 millimeters
Tempurature Rating:
-40.0 degrees celsius and 100.0 degrees celsius single response
Outside Diameter:
20.3 millimeters
Minimum Inside Bending Radius:
127.0 millimeters
Exterior Color:
Black
End Application:
Mk75 mod 0x1, mount, gun, 76 mm 62 caliber sse
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Perforated outer cover
Burst Test Pressure:
1125.0 kilograms per square centimeter
Layer Composition And Location:
1st layer braided fiber and 2nd layer braided fiber and outer layer molded polyurethane
Maximum Operating Pressure:
281.0 kilograms per square centimeter
Thread Size:
0.375 inches 1st end
Hydrostatic Test Pressure:
563.0 kilograms per square centimeter
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
178.0 millimeters
Product Name:
Hose assembly, metric

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

