

View Online at <https://aerobasegroup.com/nsn/4720-01-494-1005>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

15.875 millimeters

**Temperature Rating:**

-55.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

**Outside Diameter:**

Between 23.6982 millimeters and 24.8666 millimeters

**Minimum Inside Bending Radius:**

69.85 millimeters

**End Application:**

MEDI-UM-TAC-TICA

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

3000.0 pounds per square inch

**Maximum Operating Pressure:**

750.0 pounds per square inch

**Thread Size:**

0.875 inches 2nd end

**Seat Angle:**

45.0 degrees 2nd end

**Hydrostatic Test Pressure:**

1500.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Oil resistant and heat resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

964.8 millimeters working

**Product Name:**

Hose assembly, hub vent, front rh

**Special Features:**

Includes first end fitting 10-10 301447, second end 10-10

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0