## NSN 4720-01-494-2924

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-494-2924

Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-50.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response
Outside Diameter:
1.190 inches
Minimum Inside Bending Radius:
9.500 inches
End Application:
MEDI-UM-TAC-TICA
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
14 2nd end
Burst Test Pressure:
12400.0 pounds per square inch
Maximum Operating Pressure:
3100.0 pounds per square inch
Thread Size:
1.0625 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6200.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:

520.0 millimeters

**Measuring Method And Length:** 

Smooth

## NSN 4720-01-494-2924

**Fiig:** A542a0

Nonmetallic Hose Assembly - Page 2 of 2

