

View Online at <https://aerobasegroup.com/nsn/4720-01-494-7830>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.229 inches

Temperature Rating:

-100.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.495 inches

Minimum Inside Bending Radius:

3.000 inches

End Application:

3655-00-722-3901; generating and charging plant, oxygen-nitrogen, skid-mounted

Connection Style:

Plain optional end 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Identical

Burst Test Pressure:

24000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

6000.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

72.000 inches excluding end fittings

Special Features:

Item is complete pigtail assembly; cga cylinder connection; it is a standard oxygen pigtail

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0