Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-495-0774

Cross Sectional	I Shape:
Round	
Thread Directio	n:
Right-hand 1st e	nd
Inside Diameter	:
0.375 inches	
Tempurature Ra	ating:
-40.0 degrees fal	hrenheit and 212.0 degrees fahrenheit single response
Outside Diamet	er:
0.713 inches	
Minimum Inside	Bending Radius:
5.000 inches	
End Application	1:
Nsn2350-01-368	-9500 - carrier, ammunition, tracked - field artillery ammunition support vehicle (faagv) (m992
Connection Sty	le:
Swivel nut, flare	d 2nd end
Connection Typ	De:
Threaded interna	al tube 1st end
Layer Composit	tion And Location:
1st layer braided	wire and 2nd layer braided wire and outer layer molded rubber, synthetic
Maximum Opera	ating Pressure:
2250.0 pounds p	er square inch
Thread Size:	
0.375 inches 1st	end
Inside Surface (	Condition:
Smooth	
Measuring Meth	nod And Length:
15.000 inches	
Special Feature	s:
Nha p/n 1246320	05 - used on m992a2
Media For Whic	h Designed:
Fuel/oil, hydroca	arbon single response
Shelf Life:	
N/a	
Unit Of Measure	2:
Demilitarization	:
No	
Fiig:	
A542a0	