

View Online at <https://aerobasegroup.com/nsn/4720-01-496-8371>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-67.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

Between 0.469 inches and 0.531 inches

Minimum Inside Bending Radius:

2.250 inches

End Application:

2320-01-206-4089; truck, cargo

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 1st end

Connection Type:

Unthreaded external hose 2nd end

Burst Test Pressure:

1250.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

625.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and mildew resistant and oil resistant and ozone resistant and vibration resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

35.750 inches and 36.250 inches

Inside Diameter Hose Accommodated:

0.250 inches 2nd end

Product Name:

Hose assembly, cylinder vent

Special Features:

Interface requirement iaw sae j512 type 010110; universal female swivel with a 0.170 through passage

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Supplementary Features:

After cleaning ends of hose shall be plugged with caps or plug iaw mil-c-5501/7

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0