

View Online at <https://aerobasegroup.com/nsn/4720-01-497-5635>

Cross Sectional Shape:

Round

Inside Diameter:

0.750 inches

Outside Diameter:

1.210 inches

Minimum Inside Bending Radius:

9.500 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j517, 100r12-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

Regulator assembly, ground support

Features Provided:

Nonskive

Second End Relationship With First End:

Not identical

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire err-100

Maximum Operating Pressure:

4000.0 pounds per square inch

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Weatherproof and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Product Name:

Hose assembly -12x72 inches 37 swvl fitting hp red

Special Features:

Parker 772-12 hose; parker 10671-12-12 37 degree fitting flare swivel, crimp; parker 10643-16-16 37 degree fitting flare swivel, crimp; aeroquip 2070-16-16s 37 degree fitting flare swivel; and tag-hose 1 inch wx2 1/2 inch base plus 2 inch tail=4 1/2 inch length 0.010 aluminum

Specification Data:

Sae j517, 100r12-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0