

View Online at <https://aerobasegroup.com/nsn/4720-01-498-0225>

Cross Sectional Shape:

Round

Inside Diameter:

1.125 inches

Tempurature Rating:

-40.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

9.000 inches

End Application:

CARR-IE-R,P-ERSO

Burst Test Pressure:

2500.0 pounds per square inch single response

Layer Composition And Location:

Outer layer braided cotton cord err-100

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outer Covering Environmental Protection:

Oil resistant and fuel resistant and mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

90.000 inches

Product Name:

Coupling, tube, connector

Special Features:

working pressure varies with media mrc cqgm is for hydraulic fluid, fuel 500.0 psi, oil 50.0 psi.

Material:

Rubber synthetic tube

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541z0

Mil-std (military Standard):

Mil-h-8794 spec.