NSN 4720-01-498-2273

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-498-2273

Cross Costional Change
Cross Sectional Shape:
Round
Inside Diameter:
Between 0.367 inches and 0.398 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 0.813 inches and 0.875 inches
End Application:
Hydraulic power unit
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Internal support
Second End Relationship With First End:
Identical
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided steel wire err-100
Maximum Operating Pressure:
1000.0 pounds per square inch
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.000 inches
Special Features:
Pressure ratings due to application; fittings are cpv o'ring type; straight assembly
Media For Which Designed:
Fuel/oil, hydrocarbon single response and hydraulic fluid, phosphate-ester base single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4720-01-498-2273

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0