## NSN 4720-01-498-7911

**Cross Sectional Shape:** 

Round

**Thread Class:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-498-7911

2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.190 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response
Outside Diameter:
0.300 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
Ship, diesel engine
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.4375 inches 1st end
Seat Angle:
37.0 degrees 1st end
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.000 inches
Thread Series Designator:
Unf 1st end

## NSN 4720-01-498-7911

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0