

View Online at <https://aerobasegroup.com/nsn/4720-01-499-3299>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

2.000 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Flange Thickness:**

0.188 inches 2nd end

**Outside Diameter:**

2.900 inches

**Minimum Inside Bending Radius:**

12.500 inches

**Center To Center Distance Between Bolt Holes Along Width:**

2.375 inches 2nd end

**Center To Center Distance Between Bolt Holes Along Length:**

2.375 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

3.000 inches 2nd end

**End Application:**

Fleet combat uh-60

**Flange Width:**

3.000 inches 2nd end

**Connection Style:**

Swivel nut, gasket seal 1st end

**Bolt Hole Diameter:**

0.328 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

16 1st end

**Burst Test Pressure:**

600.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided polyester cord and outer layer braided polyester cord

**Maximum Operating Pressure:**

100.0 pounds per square inch

**Thread Size:**

2.500 inches 1st end

**Flow Angle:**

90.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

43.375 inches working

**Flange Style:**

Rectangular (includes square) 2nd end

**Special Features:**

Sikorsky standard title: hose & hose assembly, flexible ballistic tolerant, self-sealing aromatic fuel

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0