

View Online at <https://aerobasegroup.com/nsn/4720-01-499-3303>

Cross Sectional Shape:

Round

Inside Diameter:

2.000 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.188 inches 2nd end

Outside Diameter:

2.900 inches

Minimum Inside Bending Radius:

12.500 inches

Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.000 inches 2nd end

End Application:

Fleet combat uh-60

Flange Width:

3.000 inches 2nd end

Connection Style:

Plain swivel 2nd end

Bolt Hole Diameter:

0.328 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyester cord and outer layer braided polyester cord

Maximum Operating Pressure:

100.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

28.000 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Sikorsky standard title: hose & hose assembly, flexible ballistic tolerant, self-sealing aromatic fuel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0