NSN 4720-01-499-3340

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-499-3340

2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
1.704 inches
Minimum Inside Bending Radius:
9.000 inches
End Application:
Fleet combat uh-60
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting aluminum alloy all ends
Fitting Component And Surface Treatment:
Complete fitting anodize 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
1750.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire err-100
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
2.000 inches 1st end
Inside Surface Condition:
Smooth

NSN 4720-01-499-3340

No Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 13.500 inches working Special Features: Sikorsky standard title: hose assembly, medium pressure, rubber Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure: -Demilitarization: