NSN 4720-01-499-3340

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-499-3340

| 2b 1st end |
|---|
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 1.375 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.704 inches |
| Minimum Inside Bending Radius: |
| 9.000 inches |
| End Application: |
| Fleet combat uh-60 |
| Connection Style: |
| Swivel nut, gasket seal 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting aluminum alloy all ends |
| Fitting Component And Surface Treatment: |
| Complete fitting anodize 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 16 1st end |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 1750.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire err-100 |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Thread Size: |
| 2.000 inches 1st end |
| Inside Surface Condition: |
| Smooth |

NSN 4720-01-499-3340

No Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 13.500 inches working Special Features: Sikorsky standard title: hose assembly, medium pressure, rubber Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure: -Demilitarization: