NSN 4720-01-499-4223

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-499-4223

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.8125 inches
Minimum Inside Bending Radius:
7.000 inches
Hose Or Tubing Specification/std Data:
Sae j517, 100r1, type at-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
End Application:
Alq-99; used on the ea6b aircraft
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting zinc 1st end
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
8000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer molded rubber, synthetic err-100
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:

37.0 degrees 1st end

NSN 4720-01-499-4223

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
108.000 inches working
Second End Swivel Action Capability:
Not included
Product Name:
Hose assembly
Special Features:
HOSE-AN-DEN-DFIT
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Unf 1st end
Specification Data:
Sae j517, 100r1, type at-81343 national std/spec
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0