Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-499-4523

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Direction:  |
| Right-hand 2nd end   |
| Inside Diameter:   |
| 0.380 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response    |
| Outside Diameter:  |
| 0.630 inches   |
| Minimum Inside Bending Radius:   |
| 3.000 inches   |
| End Application:   |
| Alq-99; used on the ea6b aircraft  |
| Connection Style:  |
| Plain optional end 1st end   |
| End Connection Design:   |
| Straight 2nd end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Burst Test Pressure:   |
| 1000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 2nd layer braided textile yarn and outer layer molded rubber, synthetic  |
| Maximum Operating Pressure:  |
| 250.0 pounds per square inch   |
| Thread Size:   |
| 0.375 inches 2nd end   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 26.000 inches working  |
| Product Name:  |
| Hose assembly  |
| Special Features:  |
| Hose is the aeroquip p/n fc332; fittings are from swagelok p/n sl6 & pm6 |
| Media For Which Designed:  |
| Fuel/oil, hydrocarbon single response                                    |
| Thread Series Designator:  |
| Npt 2nd end  |
| Shelf Life:  |
| N/a  |
|  |

## NSN 4720-01-499-4523

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0