

View Online at <https://aerobasegroup.com/nsn/4720-01-499-5682>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.406 inches

**Temperature Rating:**

-67.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.546 inches and 0.585 inches

**Minimum Inside Bending Radius:**

4.625 inches

**Exterior Color:**

Natural

**End Application:**

Fleet combat

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

8000.0 pounds per square inch

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

20.625 inches working

**Product Name:**

Hose assembly permanently attached fittings, tetrafluorethylene high temperature medium pressure, flare to flare

**Thread Series Designator:**

Unjf 1st end

**Specification Data:**

96906-ms8005 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0