NSN 4720-01-499-6670

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-499-6670 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.940 inches **Minimum Inside Bending Radius:** 2.250 inches **Exterior Color:** Black **End Application:** VEHI-CL-E,T-RUCK **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided polyester cord and 1st layer braided polyester cord and 2nd layer braided steel wire **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Vacuum In Torr:** 50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

57.000 inches

NSN 4720-01-499-6670

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0