

View Online at <https://aerobasegroup.com/nsn/4720-01-499-6679>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.920 inches

Minimum Inside Bending Radius:

5.500 inches

Exterior Color:

Blue

End Application:

VEHI-CL-E,T-RUCK

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

7000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided polyester cord and 1st layer braided polyester cord and 2nd layer braided steel wire

Maximum Operating Pressure:

1750.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

47.000 inches

Thread Series Designator:

Unf 2nd end

Specification Data:

82343-sae j517 100r5 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0