NSN 4720-01-502-1000

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.602 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-502-1000

275.0 degrees fahrenheit single response
Outside Diameter:
Between 1.020 inches and 1.080 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
1600.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.0625 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.000 inches working
Special Features:
Sleeve length 3 inches
Media For Which Designed:
Air single response and gas single response and hydraulic fluid single response

NSN 4720-01-502-1000

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unj 2nd end
Specification Data:
81343-as117 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0