Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-502-8749

C	Cross Sectional Shape:
F	Round
٦	Thread Class:
3	3b 1st end
٦	Thread Direction:
F	Right-hand 1st end
l	nside Diameter:
C	0.355 inches
٦	Fempurature Rating:
-	65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
(Dutside Diameter:
C	0.587 inches
Ν	Ainimum Inside Bending Radius:
C	0.750 inches
E	End Application:
ŀ	Aircraft
(Connection Style:
S	Swivel nut flare 1st end
E	End Connection Design:
S	Straight 1st end
(Connection Type:
٦	Threaded internal tube 1st end
F	Features Provided:
E	Electrostatic discharge capability
E	Burst Test Pressure:
1	200.0 pounds per square inch
L	ayer Composition And Location:
1	st layer braided corrosion resistant steel wire and outer layer braided fabric
Ν	Naximum Operating Pressure:
3	300.0 pounds per square inch
٦	Fhread Size:
С	0.5625 inches 1st end
S	Seat Angle:
3	37.0 degrees 1st end
ŀ	lydrostatic Test Pressure:
	300.0 pounds per square inch
١	/acuum In Torr:
-	50.8
	Criticality Code Justification:
	Feat
-	nside Surface Condition:
(Convoluted



Measuring Method And Length: 18.875 inches working

Special Features:

Weapon system essential

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0