## NSN 4720-01-503-0808

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

0.298 inches

Thread Direction:
Right-hand 1st end
Inside Diameter:

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-503-0808

-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.475 inches
Minimum Inside Bending Radius:
2.500 inches
End Application:
Aircraft; c135
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.5625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and solvent resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.250 inches working

## NSN 4720-01-503-0808

Nonmetallic Hose Assembly - Page 2 of 2



Sı	oec	ial	Fe	atı	ur	es	:
----	-----	-----	----	-----	----	----	---

Polyester chafeguard

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A542a0