

View Online at <https://aerobasegroup.com/nsn/4720-01-503-0833>

**Temperature Rating:**

-65.0 degrees fahrenheit 1st response and 400.0 degrees fahrenheit 1st response

**Minimum Inside Bending Radius:**

2.880 inches

**End Application:**

C-135 aircraft

**Features Provided:**

Electrostatic discharge capability

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

51.250 inches

**Outside Diameter Tube Accommodated:**

0.540 inches all ends

**Special Features:**

I.D. 0.391, round shape, -65 to 400 degrees temp rating, threaded internal tube, swivel nut flare, thread class 3b, thread direction right-handed, seat angle indeg 37.0, inner conveying tube material plastic-polytetrafluoroethylene, first end connecting design-straight, second end relationship w/first end is identical; burst test pressure is 14000.0 psi, first end swivel action capability not included; first end fitting/component and material-complete fitting, operating pressure-3000.0 psi, first end fitting/component and surface treatment-complete fitting, first end thread series designator is jf, external protection type and location - chafe guard, polyester

**Supplementary Features:**

Pregnated braid first end nom thread size .750 inches, outer covering environmental protection fuel resistant, oil resistant, solvent resistant

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0