Nonmetallic Hose Assembly - Page 1 of 2



Nonmetallic Hose Assembly - Page 1 of 2	Gr
View Online at https://aerobasegroup.com/nsn/4720-01-503-1597	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.391 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response	
Outside Diameter:	
0.855 inches	
Minimum Inside Bending Radius:	
2.880 inches	
End Application:	
C-135 aircraft	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
14000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire and 1st layer spirally wrapped corrosion resistant steel fabric	and 2nd layer spirally
wrapped corrosion resistant steel fabric	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
12.0 degrees 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
11.125 inches working	
Special Features:	

Flareless cres (nas1760) fittings

Thread Series Designator:

Unjf 1st end

NSN 4720-01-503-1597

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

