Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-503-1732

| ····· ································  |
|---|
| Cross Sectional Shape:  |
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.298 inches  |
| Tempurature Rating:   |
| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.565 inches  |
| Minimum Inside Bending Radius:  |
| 2.500 inches  |
| End Application:  |
| Aircraft stratolifter, c-135  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 14000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.5625 inches 1st end   |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 6000.0 pounds per square inch   |
| Outer Covering Environmental Protection:  |
| Fuel resistant and oil resistant and solvent resistant                                |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 26.000 inches working   |
| Special Features:   |
| Polyester chafeguard  |
|   |

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0