

View Online at <https://aerobasegroup.com/nsn/4720-01-503-2482>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.391 inches

**Temperature Rating:**

-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.680 inches

**Minimum Inside Bending Radius:**

2.880 inches

**End Application:**

Aircraft stratolifter, c-135

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

14000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.7500 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and solvent resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

33.500 inches working

**Special Features:**

Polyester chafeguard

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0