## NSN 4720-01-503-2482

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches

Polyester chafeguard

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-503-2482

Tempurature Rating:				
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response				
Outside Diameter:				
0.680 inches				
Minimum Inside Bending Radius:				
2.880 inches				
End Application:				
Aircraft stratolifter, c-135				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
14000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
3000.0 pounds per square inch				
Thread Size:				
0.7500 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
6000.0 pounds per square inch				
Outer Covering Environmental Protection:				
Fuel resistant and oil resistant and solvent resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
33.500 inches working				
Special Features:				

## NSN 4720-01-503-2482

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	Design	nator:
	0000	_00.9.	

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0