## NSN 4720-01-503-2867

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-503-2867
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.490 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.780 inches
Minimum Inside Bending Radius:
3.250 inches
End Application:
Aircraft; c135
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Three districts

**Thread Size:** 

0.8750 inches 2nd end

Seat Angle:

37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

6000.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Fuel resistant and oil resistant and solvent resistant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

25.000 inches working

## NSN 4720-01-503-2867

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Des	ignator:
-------------------	----------

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0