

View Online at <https://aerobasegroup.com/nsn/4720-01-503-3344>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.875 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

Between 1.000 inches and 1.740 inches

**Minimum Inside Bending Radius:**

7.380 inches

**Exterior Color:**

Blue

**End Application:**

Aircraft, stratolifter; c-135

**Connection Style:**

Swivel nut, flareless 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and outer layer braided polyester cord

**Maximum Operating Pressure:**

1250.0 pounds per square inch

**Thread Size:**

1.3125 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

2500.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

152.000 inches random

**Special Features:**

Field attachable; for fuels, lube oil, hydraulic fluids, coolants, solvents, alcohol, pneumatic systems, skydrol

**Supplementary Features:**

Lube oil mil-h-7808, mil-I-23699, all other lube oils

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0