

View Online at <https://aerobasegroup.com/nsn/4720-01-503-3344>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

Between 1.000 inches and 1.740 inches

Minimum Inside Bending Radius:

7.380 inches

Exterior Color:

Blue

End Application:

Aircraft, stratolifter; c-135

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided polyester cord

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

1.3125 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

152.000 inches random

Special Features:

Field attachable; for fuels, lube oil, hydraulic fluids, coolants, solvents, alcohol, pneumatic systems, skydrol

Supplementary Features:

Lube oil mil-h-7808, mil-I-23699, all other lube oils

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0