Nonmetallic Hose Assembly - Page 1 of 2



Nonmetallic Hose Assembly - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4720-01-503-4318
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.485 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.720 inches
Minimum Inside Bending Radius:
3.250 inches
End Application:
C-135 aircraft - stratolifter
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and nuts drilled for lockwire
Burst Test Pressure:
1200.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and heat resistant and vibration resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
48.000 inches

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0