

View Online at <https://aerobasegroup.com/nsn/4720-01-503-4318>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.485 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.720 inches

**Minimum Inside Bending Radius:**

3.250 inches

**End Application:**

C-135 aircraft - stratolifter

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability and nuts drilled for lockwire

**Burst Test Pressure:**

1200.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and heat resistant and vibration resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

48.000 inches

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A542a0