NSN 4720-01-503-7894

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-503-7894

Cross Sectional Shape:				
Round				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.880 inches				
Tempurature Rating:				
-55.0 degrees fahrenheit and 250.0 degrees fahrenheit single response				
Outside Diameter:				
1.230 inches				
Minimum Inside Bending Radius:				
3.500 inches				
Exterior Color:				
Black				
End Application:				
2320-01-452-5579; vehicle tractor truck				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
12 1st end				
Burst Test Pressure:				
1600.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided polyester cord and 1st layer braided polyester cord and 2nd layer braided steel wire				
Maximum Operating Pressure:				
400.0 pounds per square inch				
Thread Size:				
1.3125 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
56.000 inches				
Special Features:				
Ccc a145-383 no 16 hose (fc350-16)and ccc a107a-214 straight jic end fittings; meets fmvss106 specification				
Media For Which Designed:				
Air single response				

NSN 4720-01-503-7894

Nonmetallic Hose Assembly - Page 2 of 2



ını	ead	Series	Designator
Un	1st e	end	

Shelf Life: N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0