

View Online at <https://aerobasegroup.com/nsn/4720-01-503-7896>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.880 inches

**Temperature Rating:**

-55.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

1.230 inches

**Minimum Inside Bending Radius:**

3.500 inches

**Exterior Color:**

Black

**End Application:**

2320-01-452-5579; vehicle tractor truck

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

1600.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided polyester cord and 1st layer braided polyester cord and 2nd layer braided steel wire

**Maximum Operating Pressure:**

400.0 pounds per square inch

**Thread Size:**

1.3125 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

103.100 inches

**Special Features:**

Ccc a145-256 no. 4 hose (fc300-4) and ccc a107a-208 straight jic end fittings

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0