

View Online at <https://aerobasegroup.com/nsn/4720-01-503-7896>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.880 inches

Temperature Rating:

-55.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.230 inches

Minimum Inside Bending Radius:

3.500 inches

Exterior Color:

Black

End Application:

2320-01-452-5579; vehicle tractor truck

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

1600.0 pounds per square inch

Layer Composition And Location:

Outer layer braided polyester cord and 1st layer braided polyester cord and 2nd layer braided steel wire

Maximum Operating Pressure:

400.0 pounds per square inch

Thread Size:

1.3125 inches 1st end

Seat Angle:

37.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

103.100 inches

Special Features:

Ccc a145-256 no. 4 hose (fc300-4) and ccc a107a-208 straight jic end fittings

Media For Which Designed:

Air single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0