

View Online at <https://aerobasegroup.com/nsn/4720-01-504-2590>

Cross Sectional Shape:

Round

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

0.940 inches

Minimum Inside Bending Radius:

2.250 inches

End Application:

Hatch, striked

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Maximum Operating Pressure:

1250.0 pounds per square inch

Seat Angle:

37.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.750 inches excluding end fittings

Product Name:

Assembly, flex hose

Special Features:

Hose material: rubber wire reinforced, aqp elastomer tube; assembly consist of fitting, male o-ring sea (cpv) , fitting, 7/8-14 sae 37 degrees flare swivel, flexible hose, union nut, and socket weld tailpiece

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0