

View Online at <https://aerobasegroup.com/nsn/4720-01-504-7726>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.380 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Angle Between Rigid Elbow Fittings In Deg:**

90.0

**Hose Or Tubing Specification/std Data:**

Sae100r12 standard (includes industry or association standards, individual manufactureer standards, etc.).

**First End Fitting Specification/std Data:**

Saej518 standard (includes industry or association standards, individual manufactureer standards, etc.).

**End Application:**

Nsn 5420-01-430-5403 - tank, abrams m1 - carrier bridge launching

**Connection Style:**

Plain swivel w/ gasket groove 1st end

**End Flange Construction:**

Split 1st end

**End Connection Design:**

Elbow 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

16000.0 pounds per square inch

**First End Swivel Action Capability:**

Included

**Layer Composition And Location:**

1st layer spirally laid corrosion resistant steel wire err-100

**Maximum Operating Pressure:**

4000.0 pounds per square inch

**External Protection Type And Location (non-core):**

spring guard, round stainless steel coil

**Hydrostatic Test Pressure:**

8000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

39.380 inches and 40.380 inches

**Product Name:**

Hose assembly

**Special Features:**

External protection type and location- spring guard, round stainless steel coil , inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Hydraulic fluid single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0