Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-505-0196

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.602 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	•
Outside Diameter:	
1.360 inches	
Minimum Inside Bending Radius:	
4.000 inches	
End Application:	
2350-01-087-1095	
Connection Style:	
Swivel nut, flareless 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
12 2nd end	
Burst Test Pressure:	
9000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
1.0625 inches 2nd end	
Seat Angle:	
12.0 degrees 2nd end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
21.500 inches working	

NSN 4720-01-505-0196

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:

Sleeve length 3 inch

Media For Which Designed:

Air single response and gas single response and hydraulic fluid single response

Thread Series Designator:

Unj 2nd end

Specification Data:

81343-as117 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0