NSN 4720-01-506-0966

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-506-0966

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Outside Diameter:
Between 0.594 inches and 0.656 inches
Minimum Inside Bending Radius:
3.000 inches
Hose Or Tubing Specification/std Data:
Mil-h-13444, type 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
First End Fitting Specification/std Data:
Sae j516-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
End Application:
FMTV-NS-N23-2001
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
1000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer molded rubber, chloroprene err-100
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Seat Angle:

Hydrostatic Test Pressure: 500.0 pounds per square inch

45.0 degrees 1st end

NSN 4720-01-506-0966

Nonmetallic Hose Assembly - Page 2 of 2



Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and vibration resistant and mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

71.7638 inches and 72.4724 inches

Product Name:

Wrecker intermediate axle vent

Special Features:

Inner conveying tube material-rubber, synthetic

Special Markings:

Band marker iaw mil-b-43436; hase will have a continuous yellow stripe and be marked iaw mil-h-13444

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13444 spec.