

View Online at <https://aerobasegroup.com/nsn/4720-01-506-1754>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Inside Diameter:

Between 0.220 inches and 0.280 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.470 inches and 0.530 inches

Minimum Inside Bending Radius:

3.000 inches

End Application:

NEXT-AS-SY9-3016

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Burst Test Pressure:

1600.0 pounds per square inch

Layer Composition And Location:

One layer of non-metallic braid reinforcement

Maximum Operating Pressure:

400.0 pounds per square inch

Thread Size:

0.437 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Vacuum In Torr:

50.8

Measuring Method And Length:

120.760 inches and 121.000 inches

Inside Diameter Hose Accommodated:

0.250 inches 1st end

Product Name:

Hose assembly

Hazardous Substances:

Copper

Supplementary Features:

Fittings are 1.31" long

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0