Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-506-3616

| Cross Sectional Shape: |
|--|
| Round |
| Tempurature Rating: |
| -100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Minimum Inside Bending Radius: |
| 6.500 inches |
| End Application: |
| Engine diesel gen id36ss8v-am mdls 2953f01 8 cyl and 2949f01 8 cyl |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Inside Surface Condition: |
| Smooth |
| Product Name: |
| Hose |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| |