

View Online at <https://aerobasegroup.com/nsn/4720-01-507-1668>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Outside Diameter:

Between 0.594 inches and 0.656 inches

Minimum Inside Bending Radius:

3.000 inches

Hose Or Tubing Specification/std Data:

Mil-h-13444, type 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

End Application:

Wsd fmv 2320-01-447-6345 chassis, truck

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

1000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, chloroprene err-100

Maximum Operating Pressure:

250.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and vibration resistant and mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

752.0 millimeters

Product Name:

Hose assembly

Special Features:

Fittings shall be iaw sae j516; band marker shall be iaw mil-e-43436; clean by blowing clean dry air through hose assembly, then plug/cap all ends prior to shipment

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Specification Data:

Mil-h-13444, type 1 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13444 spec.