

View Online at <https://aerobasegroup.com/nsn/4720-01-507-1679>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.500 inches

**Outside Diameter:**

0.875 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-3992, type 1, class 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Saej516 standard (includes industry or association standards, individual manufactureer standards, etc.).

**End Application:**

Wsd fmtv 2320-01-447-3893 truck, tractor

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

900.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer braided fiber err-100

**Outer Covering Environmental Protection:**

Ozone resistant and oil resistant and fuel resistant and mildew resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

339.7 millimeters

**Product Name:**

Hose assembly

**Special Features:**

Band marker shall be iaw mil-b-43436

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-3992 spec.