

View Online at <https://aerobasegroup.com/nsn/4720-01-507-5356>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.485 inches and 0.515 inches

Temperature Rating:

450.0 degrees fahrenheit single response

Outside Diameter:

Between 0.641 inches and 0.687 inches

Minimum Inside Bending Radius:

5.500 inches

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

24 2nd end

Burst Test Pressure:

7000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.000 inches working

Inside Diameter Hose Accommodated:

0.500 inches 2nd end

Outside Diameter Tube Accommodated:

0.664 inches 2nd end

Product Name:

Hose assembly permanently attached fittings, tetrafluorethylene high temperature medium pressure, flare to flare

Special Features:

Min tensile strength 2500 psi

Media For Which Designed:

Hydraulic fluid single response

Test Data Document:

96906-ms8005 standard (includes industry or association standards, individual manufactureer standards, etc.). And 81349-mil-h-27267 standard (includes industry or association standards, individual manufactureer standards, etc.). And 81349-mil-f-27272 standard (includes industry or association standards, individual manufactureer standards, etc.).

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms8005 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0