NSN 4720-01-508-1569

Cross Sectional Shape:

Corrosion resistant

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-508-1569

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.250 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
End Application:
Rq-4a
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:

NSN 4720-01-508-1569Nonmetallic Hose Assembly - Page 2 of 2



Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
9.750 inches
Product Name:
Hose assembly
Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms8005 government standard
Specification Or Standard:
1 class
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A542a0